



# GFE-SWR-LMP

## Test Lamp for GFE-SWR Flame Detectors

The non Ex GFE-SWR-LMP(TC-169/1) flame detector test lamp activates GFE-SWR series flame detectors namely: GFE-SWR-UVIR(UV/IR-210/1), GFE-SWR-UV(UV-185/5) and GFE-SWR-IR3(IR3-109/1). For all models the testing range is 4 meters. The GFE-SWR-LMP(TC-169/1) test lamp is non Ex, suitable for use in safe areas only.

### TECHNICAL SPECIFICATIONS

BATTERY CHARGER	100-240 V AC, 500 mA
BATTERY	Sealed Lead Acid battery, 12 Vdc / 2.7 Ah
BATTERY AUTONOMY	10-15 minutes under optimal conditions and continuous use
LAMP	H3, 12 Vdc / 100 W
PROTECTION	IP30
OPERATING TEMPERATURE	4°C to 40°C
COLOUR / MATERIAL	Black / ABS
DIMENSIONS (BOX)	440 (L) x 340 (W) x 280 (H) mm
WEIGHT	5 kg

### ORDER CODE

GFE-SWR-LMP	TEST LAMP FOR GFE-SWR FLAME DETECTORS NON-Ex
-------------	--