VALKYRIE CS

CONVENTIONAL WALL MOUNT SOUNDER/ BEACON

RoHS Compliant

EN54-13 CERTIFIED

CERTIFIED EN54-3

The VALKYRIE CS is a wall mounted Conventional Sounder/ Beacon with low power consumption. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20V to 30V DC
CURRENT - SOUNDER/BEACON ACTIVE	10mA - 280mW @ 28V DC
MAXIMUM SOUNDER OUTPUT	97.5 dB (@ 1 meter - 30V DC)
CABLE SIZE	0.5-2.5 mm^2
RESET/START-UP TIMES	20 seconds max.
PROTECTION CATEGORY	Type A - Indoor Use / Rating IP21C
COLOUR	Red or White
CASE MATERIAL	ABS and PC - Flame Retardant rating IL 94 V2
OPER. TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
DIMENSIONS	110 (D) x 85 (H) mm included base
WEIGHT	254g included base and 304g inc. packaging

For EN54-13 compliance, please check the control panel manual specifications.

ORDER CODE

VALKYRIE CS-WHITE	CONVENTIONAL WALL SOUNDER - WHITE	1328-CPR-0287
VALKYRIE CS-RED	CONVENTIONAL WALL SOUNDER - RED	1328-CPR-0287
VALKYRIE CSB-WHITE	CONVENTIONAL WALL SOUNDER/ BEACON - WHITE	1328-CPR-0287
VALKYRIE CSB-RED	CONVENTIONAL WALL SOUNDER/ BEACON - RED	1328-CPR-0287

CE 13

© 241120

Global Fire Equipment SA

Sítio da Barracha, Parque Industrial Municipal Caixa Postal 610-A, 8150-017 São Brás de Alportel, Portugal

Telephone: (00351) 289 896 560 / **Email:** info@globalfire-equipment.com / **Web:** www.globalfire-equipment.com